

IN THE CLAIMS:

1. (Currently Amended) A pelletizing die, comprising a pelletizing die member with a die exit side exposed to cooling fluid and a die entry side for receiving polymer fed thereto, the pelletizing die member comprising:

a plurality of polymer channels;

5 a plurality of extrusion orifices, each of said extrusion orifices being connected to a respective one of said polymer channels to form a an extrusion orifice section;

heating medium conduits forming a heating medium system, said heating medium conduits including at least one conduit adjacent to each polymer channel for heating the polymer channel; and

10 a closed thermal stabilization cavity adjacent to each extrusion orifice in an associated one of said extrusion orifice sections, said thermal stabilization cavity defining a thermal stabilization zone between said die exit side exposed to cooling fluid and said heating medium conduits allowing the polymer to remain in a liquid state up to solidification just as the polymer ~~exists~~ exits the extrusion orifice.

2. (Original) A pelletizing die according to claim 1, wherein said thermal stabilization cavity includes a space surrounding each extrusion orifice section at a location inwardly of said die exit side to provide thermal stabilization from the cooling effects of the cooling fluid.

3. (Original) A pelletizing die according to claim 1, wherein said thermal stabilization

cavity includes a space extending between each extrusion orifice section at a location inwardly of said die exit side to provide thermal stabilization from the cooling effects of the cooling fluid.

4. (Original) A pelletizing die according to claim 1, wherein said thermal stabilization cavity includes a space extending substantially circumferentially between each extrusion orifice section at a location inwardly of said die exit side to provide thermal stabilization from the cooling effects of the cooling fluid.

5. (Original) A pelletizing die according to claim 1, wherein said thermal stabilization cavity includes a space extending substantially radially between each extrusion orifice within each extrusion orifice section at a location inwardly of said die exit side to provide thermal stabilization from the cooling effects of the cooling fluid.

6. (Currently Amended) A pelletizing die according to claim 1, wherein said thermal stabilization cavity is filled with a heat transfer media that provides good heat transfer characteristics. -

7. (Original) A pelletizing die according to claim 1, wherein said thermal stabilization cavity transports heat through a convective, radiative and conductive medium.

8. (Currently Amended) A pelletizing die, comprising a pelletizing die member with a

die exit side exposed to cooling fluid and a die entry side for receiving polymer fed thereto, the pelletizing die member comprising:

a plurality of polymer channels;

5 a plurality of extrusion orifices connected to a respective one of said polymer channels to form an extrusion orifice section;

heating medium conduits forming a heating medium system, said heating medium conduits including at least one conduit adjacent to each polymer channel for heating the polymer channel; and

10 a polymer channel to extrusion orifice transition zone ~~to prevent~~ defining means for preventing melt-fracture including a polymer channel connected to each of said extrusion orifices ~~taking into account~~ having a geometry based on specific polymer characteristics with ~~appropriate geometries, related optimal~~ pressures, and flow rates that ~~will allow maximum production and~~ eliminate melt fracture of the particular polymer and ~~assure the proper~~ having
15 said polymer characteristics with thermal transition of the polymer for ~~maximum~~ optimal pellet quality.

9. (Withdrawn).

10. (Currently Amended) A pelletizing die, comprising a pelletizing die member with a die exit side exposed to cooling fluid and a die entry side for receiving polymer fed thereto, the pelletizing die member comprising:

a plurality of polymer channels;

5 a plurality of extrusion orifices connected to a respective one of said polymer channels
at an extrusion orifice transition zone to form an extrusion orifice section;

10 a heating medium system with an undivided circumferential header including an inlet and
an outlet, said undivided circumferential header feeding a heating medium conduit through a
sufficiently large even pressure drop adjacent to each polymer channel for uniformly heating the
polymer channel including a transition zone conduit between adjacent channels and adjacent to
the transition zone of each of said extrusion orifices for uniformly heating polymer in each
extrusion orifice.

11. (Currently Amended) A pelletizing die according to claim 10, wherein said heating
medium system includes a heating medium conduit radially outwardly of each extrusion orifice
section and adjacent to each of said channels with said transition zone conduits surrounding
each of said transition zone.

12. (Original) A pelletizing die according to claim 10, wherein said heating medium
system includes a heating medium conduit radially inwardly of each extrusion orifice section and
adjacent to each of said channels.

13. (Original) A pelletizing die according to claim 10, wherein said heating medium
system includes another heating medium conduit between adjacent channels.

14. (Original) A pelletizing die according to claim 10, wherein said heating medium system includes a supply heating medium conduit radially outwardly of each extrusion orifice section and adjacent to each of said channels, said supply heating medium conduit being connected to said transition zone conduits for supplying heating medium to said transition zone conduits, additional heating medium conduits between adjacent channels and an intermediate heating medium conduit radially inwardly of each extrusion orifice section and adjacent to each of said channels, said intermediate heating medium conduit being connected to said transition zone conduits and being connected to said additional heating medium conduits for transferring heating medium between said transition zone conduits and said additional heating medium conduits for even heat distribution to the polymer based on once in and once out heating medium flow.

15. (Original) A pelletizing die according to claim 14, wherein said supply conduit is an inlet header extending circumferentially about said polymer channels to provide essentially equal pressure and flow to the entry of each of said transition zone channels and with a discharge header extending circumferentially about said polymer channels and connected to each of said additional channels, said discharge header having a geometry to provide equal flow and pressure drop across each of said additional channels.

16. (Original) A pelletizing die according to claim 10, further comprising:
a thermal stabilization cavity adjacent to each extrusion orifice in an associated said

extrusion orifice section, said thermal stabilization cavity defining a thermal stabilization zone between said die exit side exposed to cooling fluid and said heating medium conduits allowing the polymer to remain in a liquid state up to solidification just as the polymer exists the extrusion orifice.

17. (Currently Amended) A pelletizing die, comprising a pelletizing die member with a die exit side exposed to cooling fluid and a die entry side for receiving polymer fed thereto, the pelletizing die member comprising:

a plurality of polymer channels;

a plurality of extrusion orifices connected to a respective one of said polymer channels to form ~~a~~ an extrusion orifice section;

heating medium conduits forming a heating medium system, said heating medium conduits including at least one conduit adjacent to each polymer channel for heating the polymer channel;

a raised extrusion orifice ring encompassing said extrusion orifice sections; and
a hard face coated onto said raised extrusion orifice ring face, said hard face having a thickness of less than 1mm. and having a hardness level greater than 800 HVO1.

18. (Original) A pelletizing die according to claim 17, further comprising:

a thermal stabilization cavity adjacent to each extrusion orifice in an associated said extrusion orifice section, said thermal stabilization cavity defining a thermal stabilization zone

between said die exit side exposed to cooling fluid and said heating medium conduits allowing
5 the polymer to remain in a liquid state up to solidification just as the polymer exists the
extrusion orifice.

19-22 (Withdrawn).

23. (New) A pelletizing die, comprising a pelletizing die member with a die exit side
exposed to cooling fluid and a die entry side for receiving polymer fed thereto, the pelletizing
die member comprising:

a plurality of polymer channels;

5 a plurality of extrusion orifices connected to a respective one of said polymer channels
at a transition zone to form an extrusion orifice section;

heating medium conduits forming a heating medium system, said heating medium
conduits including at least one conduit adjacent to each polymer channel for heating the
polymer channel and at least one transition zone conduit adjacent to said transition zone; and

10 at least a thermal stabilization cavity defined by a continuous closed surface, said cavity
being adjacent to each extrusion orifice and adjacent to said die exit side in an associated one
of said extrusion orifice sections, said thermal stabilization cavity defining a thermal stabilization
zone between said die exit side exposed to cooling fluid and said heating medium conduits
allowing the polymer to remain in a liquid state up to solidification just as the polymer exits the
15 extrusion orifice.

24. (New) A pelletizing die according to claim 23, wherein said thermal stabilization cavity includes at least one of a circular geometric space surrounding said plurality of extrusion orifice sections, a longitudinal geometric space alongside said plurality of orifice sections, and an interval-filling geometric space between each of said plurality of orifice sections, at a location inwardly of said die exit side to provide thermal stabilization from the cooling effects of the cooling fluid.

25. (New) A pelletizing die according to claim 25, wherein said thermal stabilization cavity transports heat through a convective, radiative and conductive medium.